REVISIONS		
REV	DESCRIPTION	DATE





NOTES:
1. EXCEPT FOR .200 SLOT, PART IS SYMMETRICAL.
2. .200 SLOT TO BE CENTERED BETWEEN TWO .120 HOLES.

UNLESS OTHERWISE SPECIFIED:					
DIMENSIONS ARE IN INCHES DECIMAL TOLERANCES: .X ±.030 .XX ±.015 .XXX ±.005					
ANGULAR TOL: ± 1° SURFACE ROUGHNESS: 63					
INTERNAL AND EXTERNAL SURFACE INTERSECTIONS SHALL BE UNIFORMLY FINISHED WITH CHAMFER .005/.010 X 45° OR RADIUS .005/.010. CHAMFER ALL THREADED HOLES 110° OF MAJOR DIAMETER X 45°					
MATERIAL: **.020 OF COPPER**	SIZE **A**	QTY PER ASSM: **3**	SCALE: **1:1**	SHEET **1** OF **1**	REV **A**
FINISH: **NONE**		DATE: **5/26/2004**	DRAWN BY: **C. Danaher**		

High Precision Devices

1668 Valtec Lane, Suite C, Boulder, Colorado 80301
Phone: (303) 447-2558 Fax: (303) 447-2548 Web Site: www.hpd-online.com

TITLE: **P02101-342 thermal link, port cover plat**

CONFIGURATION: **00-Default**