

5

4

3

2

1

REVISIONS			
ZONE	REV	DESCRIPTION	DATE
	B	ADDED RECESSES	6/3/2003
	C	Changed diameter	7/21/2003

D

$\phi 12.900$

SECTION C-C

C

$\phi 12.940$

45°

E

R.02 MAX

.313

30°

.130

.050

DETAIL D
SCALE 2 : 1

R.125

1.760

DETAIL E
6X @ 60 DEGREES

B

A

3X 5.620

$\phi .605$

R.02 MAX

.087

$\phi .630$

30°

DETAIL F
SCALE 2 : 1

NOTES:
1. THREE PATTERNS TO BE RECESSED .010".

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES DECIMAL TOLERANCES: .X ±.030 .XX ±.015 .XXX ±.005	
ANGULAR TOL: ± 1° SURFACE ROUGHNESS $\sqrt{}$	
INTERNAL AND EXTERNAL SURFACE INTERSECTIONS SHALL BE UNIFORMLY FINISHED WITH CHAMFER .005/.010 X 45° OR RADIUS .005/.010. CHAMFER ALL THREADED HOLES 110% OF MAJOR DIAMETER X 45°	
MATERIAL:	304 Stainless Steel
FINISH:	N/A

TITLE:	
p02101-055 Plate, LHe can top	
CONFIGURATION: 00-Default	
SIZE	QTY PER ASSM: 1
DATE: 5/19/2004	DRAWN BY: C. Danaher

High Precision Devices

1668 Valtec Lane, Suite C, Boulder, Colorado 80301
Phone: (303) 447-2558 Fax: (303) 447-2548 Web Site: www.hpd-online.com

SHEET **1** OF **1**

REV **C**